



Referencia	Stock	Dimensiones (mm)				MICRO-MINI TWIN CG	Tornillo de brida	Llave	Torsión (N • m)
		MICRO-MINI TWIN CG							
		B	WF	L24 *					
Ancho de filo de corte 1mm	Ancho de filo de corte 2mm								
SBH1030R	★	13.8	13.8	13—17.5 (14)	14—16.5 (15)	03RS-10(B),03RS-20(B)	HSC05012	HKY40R	9.5
SBH1040R	★	14.7	14.8	18—22.5 (19)	19—21.5 (20)	04RS-10(B),04RS-20(B)	HSC05012	HKY40R	9.5
SBH1050R	★	15.6	15.8	23—27.5 (24)	24—26.5 (25)	05RS-10(B),05RS-20(B)	HSC05012	HKY40R	9.5
SBH1060R	★	16.5	16.8	23—32.5 (24)	24—31.5 (25)	06RS-10(B),06RS-20(B)	HSC05012	HKY40R	9.5
SBH1070R	★	17.4	17.8	28—38 (29)	29—37 (30)	07RS-10(B),07RS-20(B)	HSC05012	HKY40R	9.5

* L24 es la longitud del voladizo para suficiente fijación, y () es la longitud recomendada para el mecanizado de acero en corte en general.
 Nota 1) La MICRO-DEC y la MICRO-MINI no pueden montarse en portaherramientas cuadrados.