

RECOMMENDED CUTTING CONDITIONS

Workpiece Material	Mild Steel ($\leq 180\text{HB}$)				Carbon Steel, Alloy Steel (180—280HB)			
	AISI 1010 etc				AISI 1045, AISI 4140 etc			
Recommended grinding fluid	Water-insoluble				Water-insoluble			
Dia. DC (mm)	Cutting Speed (m/min)	Revolution (min ⁻¹)	Feed rate (Min.—Max.) (mm/rev)	Table Feed (mm/min)	Cutting Speed (m/min)	Revolution (min ⁻¹)	Feed rate (Min.—Max.) (mm/rev)	Table Feed (mm/min)
0.8	50	19800	0.01 (0.005—0.016)	195	40	15900	0.01 (0.005—0.016)	155
1.0	50	15900	0.01 (0.007—0.020)	155	40	12700	0.01 (0.007—0.020)	125
1.2	60	15900	0.015 (0.008—0.024)	235	50	13200	0.015 (0.008—0.024)	195
1.6	60	11900	0.02 (0.011—0.032)	235	50	9900	0.02 (0.011—0.032)	195
2.0	60	9500	0.025 (0.013—0.040)	235	50	7900	0.025 (0.013—0.040)	195
2.5	70	8900	0.03 (0.017—0.050)	265	60	7600	0.03 (0.017—0.050)	225
3.0	70	7400	0.04 (0.020—0.060)	295	60	6300	0.04 (0.020—0.060)	250

Workpiece Material	Carbon Steel, Alloy Steel (280—350HB)				Austenitic Stainless Steel (≤200HB)			
	AISI 4340 etc				AISI 304, AISI 316 etc			
Recommended grinding fluid	Water-insoluble				Water-insoluble			
Dia. DC (mm)	Cutting Speed (m/min)	Revolution (min ⁻¹)	Feed rate (Min.—Max.) (mm/rev)	Table Feed (mm/min)	Cutting Speed (m/min)	Revolution (min ⁻¹)	Feed rate (Min.—Max.) (mm/rev)	Table Feed (mm/min)
0.8	30	11900	0.005 (0.004—0.005)	55	30	11900	0.01 (0.005—0.016)	115
1.0	30	9500	0.005 (0.005—0.007)	45	30	9500	0.01 (0.007—0.020)	95
1.2	40	10600	0.005 (0.006—0.008)	50	30	7900	0.015 (0.008—0.024)	115
1.6	40	7900	0.01 (0.008—0.011)	75	40	7900	0.02 (0.011—0.032)	155
2.0	40	6300	0.01 (0.010—0.013)	60	40	6300	0.025 (0.013—0.040)	155
2.5	50	6300	0.015 (0.013—0.017)	90	40	5000	0.03 (0.017—0.050)	150
3.0	50	5300	0.015 (0.015—0.020)	75	40	4200	0.04 (0.020—0.060)	165

Workpiece Material	Gray Cast Iron (≤350MPa)				Ductile Cast Iron (≤450MPa)			
	No 45 B etc				60-40-8 etc			
Recommended grinding fluid	Water-insoluble				Water-insoluble			
	Water-soluble				Water-soluble			
Dia. DC (mm)	Cutting Speed (m/min)	Revolution (min ⁻¹)	Feed rate (Min.—Max.) (mm/rev)	Table Feed (mm/min)	Cutting Speed (m/min)	Revolution (min ⁻¹)	Feed rate (Min.—Max.) (mm/rev)	Table Feed (mm/min)
0.8	50	19800	0.01 (0.008—0.016)	195	40	15900	0.005 (0.005—0.008)	75
1.0	50	15900	0.015 (0.010—0.020)	235	40	12700	0.005 (0.007—0.010)	60
1.2	60	15900	0.015 (0.012—0.024)	235	50	13200	0.01 (0.008—0.012)	130
1.6	60	11900	0.02 (0.016—0.032)	235	50	9900	0.01 (0.011—0.016)	95
2.0	60	9500	0.03 (0.020—0.040)	285	50	7900	0.015 (0.013—0.020)	115
2.5	70	8900	0.035 (0.025—0.050)	310	60	7600	0.02 (0.017—0.025)	150
3.0	70	7400	0.045 (0.030—0.060)	330	60	6300	0.025 (0.020—0.030)	155

Workpiece Material	Aluminium Alloys (Si<5%)				Copper, Copper alloys			
	Water-insoluble Water-soluble				Water-insoluble Water-soluble			
Dia. DC (mm)	Cutting Speed (m/min)	Revolution (min ⁻¹)	Feed rate (Min.—Max.) (mm/rev)	Table Feed (mm/min)	Cutting Speed (m/min)	Revolution (min ⁻¹)	Feed rate (Min.—Max.) (mm/rev)	Table Feed (mm/min)
0.8	50	19800	0.01 (0.008—0.016)	195	40	15900	0.01 (0.008—0.016)	155
1.0	60	19000	0.015 (0.010—0.020)	285	50	15900	0.015 (0.010—0.020)	235
1.2	70	18500	0.015 (0.012—0.024)	275	60	15900	0.015 (0.012—0.024)	235
1.6	80	15900	0.02 (0.016—0.032)	315	70	13900	0.02 (0.016—0.032)	275
2.0	90	14300	0.03 (0.020—0.040)	425	80	12700	0.03 (0.020—0.040)	380
2.5	100	12700	0.035 (0.025—0.050)	440	90	11400	0.035 (0.025—0.050)	395
3.0	100	10600	0.045 (0.030—0.060)	475	100	10600	0.045 (0.030—0.060)	475

Note 1) Requires a guide bush or pilot hole.

Note 2) Coolant filter must be less than 5 microns. Fine filtration is necessary to prevent blockage of the coolant holes.

Note 3) For safety and success, high pressure coolant is required. (Minimum coolant pressure=1,000PSI)