

## RECOMMENDED CUTTING CONDITIONS

Work material	Carbon steel, Cast iron, Alloy steel (–30HRC)			Alloy steel, Tool steel, Pre-hardened steel			Austenitic stainless steel, Titanium alloy			Hardened steel (45–55HRC)		
	AISI 1050, AISI 35, AISI P20 etc.			AISI H13, AISI W1-10, AISI P21 etc.			AISI 304, AISI 306, Ti-6Al-4V etc.			AISI H13 etc.		
DC (mm)	Revolution (min <sup>-1</sup> )	Table feed		Revolution (min <sup>-1</sup> )	Table feed		Revolution (min <sup>-1</sup> )	Table feed		Revolution (min <sup>-1</sup> )	Table feed	
		(mm/min)	(IPM)		(mm/min)	(IPM)		(mm/min)	(IPM)		(mm/min)	(IPM)
0.1	40000	— (40)	— (1.6)	40000	— (40)	— (1.6)	40000	— (35)	— (1.4)	40000	— (25)	— (1.0)
0.2	40000	— (45)	— (1.8)	40000	— (45)	— (1.8)	40000	— (35)	— (1.4)	32000	— (25)	— (1.0)
0.3	40000	— (55)	— (2.2)	32000	— (45)	— (1.8)	27000	— (35)	— (1.4)	21000	— (25)	— (1.0)
0.4	32000	— (60)	— (2.4)	24000	— (45)	— (1.8)	20000	— (35)	— (1.4)	16000	— (25)	— (1.0)
0.5	25000	— (60)	— (2.4)	19000	— (45)	— (1.8)	16000	— (35)	— (1.4)	13000	— (25)	— (1.0)
0.6	21000	— (60)	— (2.4)	16000	— (45)	— (1.8)	13000	— (35)	— (1.4)	11000	— (25)	— (1.0)
0.7	18000	— (60)	— (2.4)	14000	— (45)	— (1.8)	11000	— (35)	— (1.4)	9100	— (25)	— (1.0)
0.8	16000	— (60)	— (2.4)	12000	— (45)	— (1.8)	9900	— (35)	— (1.4)	8000	— (25)	— (1.0)
0.9	14000	— (60)	— (2.4)	11000	— (45)	— (1.8)	8800	— (35)	— (1.4)	7100	— (25)	— (1.0)
1	13000	60 (60)	2.4 (2.4)	9500	45 (45)	1.8 (1.8)	8000	35 (35)	1.4 (1.4)	6400	25 (25)	1.0 (1.0)
1.5	8500	60 (60)	2.4 (2.4)	6400	45 (45)	1.8 (1.8)	5300	35 (35)	1.4 (1.4)	4200	25 (25)	1.0 (1.0)
2	6400	60 (60)	2.4 (2.4)	4800	45 (45)	1.8 (1.8)	4000	35 (35)	1.4 (1.4)	3200	25 (25)	1.0 (1.0)
2.5	5100	60 (60)	2.4 (2.4)	3800	45 (45)	1.8 (1.8)	3200	40 (40)	1.6 (1.6)	2500	25 (25)	1.0 (1.0)
3	4200	65 (60)	2.6 (2.4)	3400	55 (45)	2.2 (1.8)	2600	40 (40)	1.6 (1.6)	2100	25 (25)	1.0 (1.0)
4	3400	80 (60)	3.1 (2.4)	2700	65 (45)	2.6 (1.8)	2100 (1600)	50 (30)	2.0 (1.2)	1700	35 (25)	1.4 (1.0)
5	2900	100 (60)	3.9 (2.4)	2300	80 (45)	3.1 (1.8)	1800 (1350)	60 (30)	2.4 (1.2)	1500	40 (25)	1.6 (1.0)
6	2500	120 (60)	4.7 (2.4)	2000	100 (50)	3.9 (2.0)	1500 (1100)	75 (30)	3.0 (1.2)	1300	50 (25)	2.0 (1.0)
8	1900	130 (60)	5.1 (2.4)	1500	100 (50)	3.9 (2.0)	1200 (900)	80 (30)	3.1 (1.2)	1000	50 (25)	2.0 (1.0)
10	1600	130 (60)	5.1 (2.4)	1300	100 (50)	3.9 (2.0)	950 (710)	75 (30)	3.0 (1.2)	800	50 (25)	2.0 (1.0)
12	1300	120 (60)	4.7 (2.4)	1100	100 (50)	3.9 (2.0)	800 (600)	75 (30)	3.0 (1.2)	670	50 (25)	2.0 (1.0)

  

Depth of cut	Standard cutting conditions		Slotting conditions	
	DC	Table feed	DC	Table feed
DC ≥ φ1	≤0.05DC (MAX.0.5mm)	≤2.5DC	≤0.02DC	≤2DC
	DC	DC	DC	DC
DC < φ1	≤0.02DC (DC < φ0.5)	≤0.05DC (φ0.5 ≤ DC < φ1)	≤0.02DC (DC < φ0.5)	≤0.05DC (DC ≥ φ0.5)
	≤0.1DC (φ1 ≤ DC < φ2)	≤0.2DC (DC ≥ φ2)	≤0.1DC (φ1 ≤ DC < φ2)	≤0.05DC (DC ≥ φ0.5)
	DC	DC	DC	DC
	DC	DC	DC	DC

( ) : Indicates standard revolution and feed rate in slotting.

- 1) When cutting austenitic stainless steels, the use of water-soluble cutting fluid is especially effective.
- 2) If the depth of cut is smaller than this table, feed rate can be increased.
- 3) When drilling, please set the feed rate at 1/3 or below of the above value.
- 4) If the rigidity of the machine or the workpiece installation is very low, or chattering is generated, please reduce the revolution and the feed rate proportionately.