

# Identification(Shoulder Milling)

Reduce the cutting parameters by the coefficient values shown according to the length of overhang.  
 For long edge and oversize types heads refer to their specific recommended conditions.

(inch)

L/D	Carbon Steels, Alloy Steels, Mild Steels, Copper, Copper Alloys			Pre-hardened Steels, Carbon Steels, Alloy Steels, Alloy Tool Steels			Austenitic Stainless Steels, Ferritic and Martensitic Stainless Steels, Titanium Alloys		
	Revolution n (min <sup>-1</sup> )	Feed per Tooth fz (IPT)	Width of Cut ae	Revolution n (min <sup>-1</sup> )	Feed per Tooth fz (IPT)	Width of Cut ae	Revolution n (min <sup>-1</sup> )	Feed per Tooth fz (IPT)	Width of Cut ae
<b>2</b>	100%	100%	100%	100%	100%	100%	100%	100%	100%
<b>3</b>	100%	100%	100%	100%	100%	100%	100%	100%	100%
<b>4</b>	80%	90%	70%	80%	90%	70%	80%	90%	70%
<b>5</b>	60%	80%	40%	60%	80%	40%	60%	80%	40%
<b>6</b>	50%	70%	30%	50%	70%	30%	50%	70%	30%
<b>7</b>	40%	70%	20%	40%	70%	20%	30%	60%	20%
<b>8</b>	40%	60%	10%	40%	60%	10%	30%	50%	10%
<b>9</b>	30%	60%	10%	30%	60%	10%	20%	50%	10%

L/D	Precipitation Hardening Stainless Steels, Cobalt Chromium Alloys			Heat Resistant Alloys Inconel718		
	Revolution n (min <sup>-1</sup> )	Feed per Tooth fz (IPT)	Width of Cut ae	Revolution n (min <sup>-1</sup> )	Feed per Tooth fz (IPT)	Width of Cut ae
<b>2</b>	100%	100%	100%	100%	100%	100%
<b>3</b>	100%	100%	100%	100%	100%	100%
<b>4</b>	80%	90%	70%	80%	90%	70%
<b>5</b>	60%	80%	40%	60%	80%	40%
<b>6</b>	50%	70%	30%	50%	70%	30%
<b>7</b>	30%	60%	20%	30%	60%	20%
<b>8</b>	30%	50%	10%	30%	50%	10%
<b>9</b>	20%	50%	10%	20%	50%	10%

# ***IMX-54HV/IMX-54HV-S/IMX-C4HV/IMX-C4HV-S***

Square/Corner radius head, 4 flute, Irregular helix (With/Without coolant hole)

## Recommended Cutting Conditions

### Shoulder Milling

(inch)

Workpiece Material	Carbon Steels, Alloy Steels, Mild Steels, Copper, Copper Alloys				Pre-hardened Steels, Carbon Steels, Alloy Steels, Alloy Tool Steels				Austenitic Stainless Steels, Ferritic and Martensitic Stainless Steels, Titanium Alloys				
	DC (mm) (inch)	Revolution n (min <sup>-1</sup> )	Feed Rate vf (IPM)	Depth of Cut ap	Width of Cut ae	Revolution n (min <sup>-1</sup> )	Feed Rate vf (IPM)	Depth of Cut ap	Width of Cut ae	Revolution n (min <sup>-1</sup> )	Feed Rate vf (IPM)	Depth of Cut ap	Width of Cut ae
	<b>.3750</b>	5000	70.0	.375	.075	4000	38.4	.375	.075	3400	40.8	.375	.075
	<b>10 .3937</b>	4800	67.2	.394	.079	3800	36.5	.394	.079	3200	38.4	.394	.079
	<b>12 .4724</b>	4000	56.0	.472	.094	3200	33.3	.472	.094	2700	33.5	.472	.094
	<b>.5000</b>	3700	51.8	.500	.100	3000	31.2	.500	.100	2500	31.0	.500	.100
	<b>.6250</b>	3000	46.8	.625	.125	2400	28.8	.625	.125	2000	28.0	.625	.125
	<b>16 .6299</b>	3000	46.8	.630	.126	2400	28.8	.630	.126	2000	28.0	.630	.126
	<b>.7500</b>	2500	39.0	.750	.150	2000	24.0	.750	.150	1700	23.8	.750	.150
	<b>20 .7874</b>	2400	37.4	.787	.157	1900	22.8	.787	.157	1600	22.4	.787	.157
	<b>25 .9843</b>	1900	35.7	.984	.197	1500	18.0	.984	.197	1300	18.2	.984	.197
	<b>1.0000</b>	1900	35.7	1.000	.200	1500	18.0	1.000	.200	1300	18.2	1.000	.200
Depth of Cut													

Workpiece Material	Precipitation Hardening Stainless Steels, Cobalt Chromium Alloys				Heat Resistant Alloys Inconel718				
	DC (mm) (inch)	Revolution n (min <sup>-1</sup> )	Feed Rate vf (IPM)	Depth of Cut ap	Width of Cut ae	Revolution n (min <sup>-1</sup> )	Feed Rate vf (IPM)	Depth of Cut ap	Width of Cut ae
	<b>.3750</b>	2500	24.0	.375	.075	1300	8.3	.375	.038
	<b>10 .3937</b>	2400	23.0	.394	.079	1300	8.3	.394	.039
	<b>12 .4724</b>	2000	20.8	.472	.094	1100	7.9	.472	.047
	<b>.5000</b>	1900	19.8	.500	.100	990	7.1	.500	.050
	<b>.6250</b>	1500	18.0	.625	.125	790	6.3	.625	.063
	<b>16 .6299</b>	1500	18.0	.630	.126	790	6.3	.630	.063
	<b>.7500</b>	1200	14.4	.750	.150	660	5.3	.750	.075
	<b>20 .7874</b>	1200	14.4	.787	.157	630	5.0	.787	.079
	<b>25 .9843</b>	950	11.4	.984	.197	500	4.1	.984	.098
	<b>1.0000</b>	940	11.3	1.000	.200	500	4.0	1.000	.100
Depth of Cut									

Note 1) The irregular helix flute end mill has a larger effect on controlling vibration when compared to standard end mills. However, if the rigidity of the machine or the workpiece material installation is poor, vibration or abnormal sound can occur.

In this case, please reduce the revolution and the feed rate proportionately, or set a lower depth of cut.

Note 2) If the depth of cut is smaller, the revolution and the feed rate can be increased.


Note 3) For stainless steels, titanium alloys and heat resistant alloys, the use of water-soluble coolant is effective.

## Slot Milling

(inch)

Workpiece Material	Carbon Steels, Alloy Steels, Mild Steels, Copper, Copper Alloys			Pre-hardened Steels, Carbon Steels, Alloy Steels, Alloy Tool Steels			Austenitic Stainless Steels, Ferritic and Martensitic Stainless Steels, Titanium Alloys			
	DC (mm) (inch)	Revolution $n$ (min <sup>-1</sup> )	Feed Rate $vf$ (IPM)	Depth of Cut $ap$	Revolution $n$ (min <sup>-1</sup> )	Feed Rate $vf$ (IPM)	Depth of Cut $ap$	Revolution $n$ (min <sup>-1</sup> )	Feed Rate $vf$ (IPM)	Depth of Cut $ap$
	.3750	3400	21.4	.188	2600	12.5	.188	2500	12.0	.188
10	.3937	3200	20.5	.197	2500	12.0	.197	2400	11.5	.197
12	.4724	2700	21.6	.236	2100	13.4	.236	2000	12.8	.236
	.5000	2500	20.0	.250	2000	12.8	.250	1900	12.2	.250
	.6250	2000	22.4	.313	1600	12.8	.313	1500	14.4	.313
16	.6299	2000	22.4	.315	1600	12.8	.315	1500	14.4	.315
	.7500	1700	19.0	.375	1300	10.4	.375	1200	11.5	.375
20	.7874	1600	17.9	.394	1300	10.4	.394	1200	11.5	.394
25	.9843	1300	16.1	.472	1000	8.0	.472	950	9.1	.472
	1.0000	1300	16.1	.480	990	7.9	.480	940	9.0	.480


Depth of Cut



DC=Dia.

Workpiece Material	Precipitation Hardening Stainless Steels, Cobalt Chromium Alloys			Heat Resistant Alloys Inconel718			
	DC (mm) (inch)	Revolution $n$ (min <sup>-1</sup> )	Feed Rate $vf$ (IPM)	Depth of Cut $ap$	Revolution $n$ (min <sup>-1</sup> )	Feed Rate $vf$ (IPM)	Depth of Cut $ap$
	.3750	2000	8.0	.188	1000	3.2	.075
10	.3937	1900	7.6	.197	970	3.1	.079
12	.4724	1600	9.0	.236	810	3.9	.094
	.5000	1500	8.4	.250	760	3.6	.100
	.6250	1200	9.6	.313	610	4.9	.125
16	.6299	1200	9.6	.315	610	4.9	.126
	.7500	1000	7.9	.375	510	4.1	.150
20	.7874	950	7.6	.394	490	3.9	.157
25	.9843	760	6.1	.472	390	3.1	.197
	1.0000	740	5.9	.480	380	3.0	.200

Depth of Cut



DC=Dia.

Note 1) The irregular helix flute end mill has a larger effect on controlling vibration when compared to standard end mills. However, if the rigidity of the machine or the workpiece material installation is poor, vibration or abnormal sound can occur.

In this case, please reduce the revolution and the feed rate proportionately, or set a lower depth of cut.

Note 2) If the depth of cut is smaller, the revolution and the feed rate can be increased.

Note 3) For stainless steels, titanium alloys and heat resistant alloys, the use of water-soluble coolant is effective.


# iMX-54HV/iMX-C4HV


Square/Corner radius head, 4 flute, Irregular helix, Long cutting edge type

## Recommended Cutting Conditions

### Shoulder Milling

(inch)

Workpiece Material		Carbon Steels, Alloy Steels, Mild Steels, Copper, Copper Alloys				Pre-hardened Steels, Carbon Steels, Alloy Steels, Alloy Tool Steels				Austenitic Stainless Steels, Ferritic and Martensitic Stainless Steels, Titanium Alloys			
L/D	DC (mm)	Revolution n (min <sup>-1</sup> )	Feed Rate vf (IPM)	Depth of Cut ap	Width of Cut ae	Revolution n (min <sup>-1</sup> )	Feed Rate vf (IPM)	Depth of Cut ap	Width of Cut ae	Revolution n (min <sup>-1</sup> )	Feed Rate vf (IPM)	Depth of Cut ap	Width of Cut ae
4	16	2000	28.0	1.260	.031	1600	17.9	1.260	.031	1200	14.9	1.260	.031
	20	1600	22.4	1.575	.039	1300	14.6	1.575	.039	950	11.8	1.575	.039
6	16	1200	13.4	1.260	.031	990	8.0	1.260	.031	790	7.6	1.260	.031
	20	950	10.6	1.575	.039	800	6.4	1.575	.039	630	6.0	1.575	.039
Depth of Cut													

Workpiece Material		Precipitation Hardening Stainless Steels, Cobalt Chromium Alloys				Heat Resistant Alloys Inconel718			
L/D	DC (mm)	Revolution n (min <sup>-1</sup> )	Feed Rate vf (IPM)	Depth of Cut ap	Width of Cut ae	Revolution n (min <sup>-1</sup> )	Feed Rate vf (IPM)	Depth of Cut ap	Width of Cut ae
4	16	1000	11.2	1.260	.031	610	4.9	1.260	.016
	20	800	9.0	1.575	.039	490	3.9	1.575	.020
6	16	610	4.9	1.260	.031	390	2.5	1.260	.016
	20	490	3.9	1.575	.039	320	2.0	1.575	.020
Depth of Cut									

Note 1) The irregular helix flute end mill has a larger effect on controlling vibration when compared to standard end mills. However, if the rigidity of the machine or the workpiece material installation is poor, vibration or abnormal sound can occur.

In this case, please reduce the revolution and the feed rate proportionately, or set a lower depth of cut.

Note 2) If the depth of cut is smaller, the revolution and the feed rate can be increased.

Note 3) L/D will be +1 when using a long cutting edge type head.


Note 4) For stainless steels, titanium alloys and heat resistant alloys, the use of water-soluble coolant is effective.

# IMX-54HV/IMX-C4HV

Square/Corner radius head, 4 flute, Irregular helix, Oversize type head

## Shoulder Milling

(inch)

Workpiece Material		Carbon Steels, Alloy Steels, Mild Steels, Copper, Copper Alloys				Pre-hardened Steels, Carbon Steels, Alloy Steels, Alloy Tool Steels				Austenitic Stainless Steels, Ferritic and Martensitic Stainless Steels, Titanium Alloys			
L/D	DC (mm)	Revolution n (min <sup>-1</sup> )	Feed Rate vf (IPM)	Depth of Cut ap	Width of Cut ae	Revolution n (min <sup>-1</sup> )	Feed Rate vf (IPM)	Depth of Cut ap	Width of Cut ae	Revolution n (min <sup>-1</sup> )	Feed Rate vf (IPM)	Depth of Cut ap	Width of Cut ae
3	11	4300	60.2	.433	.043	3500	33.6	.433	.043	2900	34.8	.433	.043
	12	4000	56.0	.472	.047	3200	30.7	.472	.047	2700	32.4	.472	.047
	13	3700	51.8	.512	.051	2900	30.2	.512	.051	2500	31.0	.512	.051
	14	3400	47.6	.551	.055	2700	28.1	.551	.055	2300	28.5	.551	.055
	17	2800	43.7	.669	.067	2300	27.6	.669	.067	1900	23.6	.669	.067
	18	2600	40.6	.709	.071	2100	25.2	.709	.071	1800	25.2	.709	.071
	22	2200	34.3	.866	.087	1700	20.4	.866	.087	1500	21.0	.866	.087
	28	1700	32.0	1.102	.110	1400	16.8	1.102	.110	1100	15.4	1.102	.110
	30	1600	30.1	1.181	.118	1300	15.6	1.181	.118	1100	15.4	1.181	.118
	32	1500	28.2	1.260	.126	1200	14.4	1.260	.126	1000	14.0	1.260	.126
5	11	2600	29.1	.433	.016	2000	16.0	.433	.016	1700	16.3	.433	.016
	12	2400	26.9	.472	.020	1900	15.2	.472	.020	1600	15.4	.472	.020
	13	2200	24.6	.512	.020	1700	13.6	.512	.020	1500	14.4	.512	.020
	14	2000	22.4	.551	.024	1600	12.8	.551	.024	1400	13.4	.551	.024
	17	1700	21.1	.669	.028	1300	12.5	.669	.028	1100	12.3	.669	.028
	18	1600	19.8	.709	.028	1200	11.5	.709	.028	1100	12.3	.709	.028
	22	1300	16.1	.866	.035	1000	9.6	.866	.035	860	9.6	.866	.035
	28	1000	15.6	1.102	.043	800	7.7	1.102	.043	680	7.6	1.102	.043
	30	950	14.8	1.181	.047	740	7.1	1.181	.047	630	7.1	1.181	.047
	32	890	13.9	1.260	.051	700	6.7	1.260	.051	590	6.6	1.260	.051
7	11	1700	16.3	.433	.008	1500	9.6	.433	.008	930	7.4	.433	.008
	12	1600	15.4	.472	.008	1300	8.3	.472	.008	850	6.8	.472	.008
	13	1500	14.4	.512	.012	1200	9.6	.512	.012	780	7.5	.512	.012
	14	1400	13.4	.551	.012	1100	8.8	.551	.012	730	7.0	.551	.012
	17	1100	12.3	.669	.012	940	7.5	.669	.012	600	5.8	.669	.012
	18	1100	12.3	.709	.016	890	7.1	.709	.016	570	5.5	.709	.016
	22	860	9.6	.866	.016	730	5.8	.866	.016	460	4.4	.866	.016
	28	680	8.4	1.102	.024	570	4.6	1.102	.024	360	3.5	1.102	.024
	30	630	7.8	1.181	.024	530	4.2	1.181	.024	340	3.3	1.181	.024
	32	590	7.3	1.260	.024	500	4.0	1.260	.024	320	3.1	1.260	.024
Depth of Cut													

Note 1) The irregular helix flute end mill has a larger effect on controlling vibration when compared to standard end mills. However, if the rigidity of the machine or the workpiece material installation is poor, vibration or abnormal sound can occur.

In this case, please reduce the revolution and the feed rate proportionately, or set a lower depth of cut.

Note 2) If the depth of cut is smaller, the revolution and the feed rate can be increased.

Note 3) For stainless steels, titanium alloys and heat resistant alloys, the use of water-soluble coolant is effective.

# IMX-54HV/IMX-C4HV

Square/Corner radius head, 4 flute, Irregular helix, Oversize type head

## Recommended Cutting Conditions

### Shoulder Milling

(inch)

L/D		Precipitation Hardening Stainless Steels, Cobalt Chromium Alloys				Heat Resistant Alloys  Inconel718			
		Revolution n (min <sup>-1</sup> )	Feed Rate vf (IPM)	Depth of Cut ap	Width of Cut ae	Revolution n (min <sup>-1</sup> )	Feed Rate vf (IPM)	Depth of Cut ap	Width of Cut ae
3	11	2200	21.1	.433	.043	880	5.6	.433	.032
	12	2000	19.2	.472	.047	810	5.2	.472	.035
	13	1800	18.7	.512	.051	750	5.4	.512	.039
	14	1700	17.7	.551	.055	690	5.0	.551	.043
	17	1400	14.6	.669	.067	740	5.3	.669	.051
	18	1300	15.6	.709	.071	700	5.6	.709	.055
	22	1100	13.2	.866	.087	570	4.6	.866	.067
	28	850	10.2	1.102	.110	450	3.6	1.102	.083
	30	790	9.5	1.181	.118	420	3.4	1.181	.091
	32	740	8.9	1.260	.126	390	3.1	1.260	.094
5	11	1500	12.0	.433	.016	310	1.5	.433	.012
	12	1300	10.4	.472	.020	280	1.3	.472	.016
	13	1200	9.6	.512	.020	260	1.7	.512	.016
	14	1100	8.8	.551	.024	240	1.5	.551	.016
	17	940	9.0	.669	.028	340	2.2	.669	.020
	18	890	8.5	.709	.028	320	2.0	.709	.024
	22	730	7.0	.866	.035	260	1.7	.866	.028
	28	570	5.5	1.102	.043	210	1.3	1.102	.031
	30	530	5.1	1.181	.047	190	1.2	1.181	.035
	32	500	4.8	1.260	.051	180	1.2	1.260	.039
7	11	710	4.5	.433	.008	—	—	—	—
	12	650	4.2	.472	.008	—	—	—	—
	13	600	4.8	.512	.012	—	—	—	—
	14	550	4.4	.551	.012	—	—	—	—
	17	460	3.7	.669	.012	—	—	—	—
	18	430	3.4	.709	.016	—	—	—	—
	22	350	2.8	.866	.016	—	—	—	—
	28	280	2.2	1.102	.024	—	—	—	—
	30	260	2.1	1.181	.024	—	—	—	—
	32	240	1.9	1.260	.024	—	—	—	—
Depth of Cut									

Note 1) The irregular helix flute end mill has a larger effect on controlling vibration when compared to standard end mills. However, if the rigidity of the machine or the workpiece material installation is poor, vibration or abnormal sound can occur.

In this case, please reduce the revolution and the feed rate proportionately, or set a lower depth of cut.

Note 2) If the depth of cut is smaller, the revolution and the feed rate can be increased.

Note 3) For stainless steels, titanium alloys and heat resistant alloys, the use of water-soluble coolant is effective.